

Rittal – The System.

Faster – better – everywhere.



SK 3285.700 Pleated filter

State: 2024-09-27 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3285.700 - Pleated filter for filter and roof-mounted fans, cooling units and chillers

Compared to conventional fleece filters, the high-quality folded filter technology enables a significant increase in the volume flow and thus an increase in the performance of the unit as well as a reduction in energy consumption. In addition, better filtration properties ensure less dust in the enclosure or unit, and the longer service life means significantly lower service costs.

Features

Model No.	SK 3285.700
Version	for cooling units
Product description	To achieve a protection category of IP 54 with the Blue e+ roof-mounted cooling unit and the VX25 Blue e+ integrated solution.
Material	Non-woven fabric
Note	Operation without a pleated filter is not permitted.
Suitable for Model No.	3185.030 3185.730
Dimensions	Width: 652 mm Height: 158 mm Depth: 15 mm
Filter class	to DIN EN 779: G4
Protection category IP to IEC 60529	IP54 when mounted in the cooling unit
Weight/packaging unit	0.02 kg
Packaging unit	3 pc(s).
Net weight	0.45
Gross weight	0.5
Customs tariff number	56039390
EAN	4028177938939
ETIM 8	EC002513

Features

ETIM 7.0	EC002513
----------	----------

ECLASS 8.0	27180706
------------	----------