

Rittal – The System.

Faster – better – everywhere.



CP 8015.401 Comfort Panel

State: 2024-09-27 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CP 8015.401 - Comfort Panel

Operating housing in a stylish / slimline design made from extruded aluminium sections for effective heat dissipation, with support arm cut-out Ø 130 mm or rectangular 120 x 65 mm to fit support arm system CP 60 / 120 / 180, service access from the front or rear, uniform all-round mounting channels for individual installation of accessories without machining, protection category IP 65. For the North American market, we have enhanced our product offerings to include the below additional size options.

Features

Model No.	CP 8015.401
Benefits	Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material	Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic
Color	Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024
Supply includes	Seals and assembly components for front panels
Suitable for front panel width	450 mm
Note	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C
OUT_SUITABLE_FOR_FRONT_PANEL_HEIGHT	350 mm
Packaging unit	1 pc(s).
Weight/packaging unit	11.4 kg
Net weight	30.999
Gross weight	30.999

Features

Customs tariff number	7326909099
-----------------------	------------

UPC-Code	86876
----------	-------

Approvals

Approvals	UL + C-UL (listed)
-----------	--------------------