Rittal – The System.

Faster – better – everywhere.






SK 3238.300 Blue e+ outlet filter


State: 30/06/2024 (Source: rittal.com/com-en)



SK 3238.300 - Blue e+ outlet filter

For ventilation by convection, an outlet filter can be fitted in both the upper and lower sections of the enclosure.





Features

Model No.	SK 3238.300
Benefits	Easy filter changes, thanks to a new opening mechanism on the
	louvred grille
	Faster installation on the enclosure with optimised detent hooks
	Tool-free assembly
Colour	RAL 7035
Supply includes	Outlet filter
	Pleated filter
Mounting cut-out	Cut-out width: 124 mm
	Cut-out height: 124 mm
To fit Model No.	SK 3238.7xx
Dimensions	Width: 148.5 mm
	Height: 148.5 mm
	Depth: 34.2 mm
Protection category NEMA	Type 1 with pleated filter
	Type 12 with chopped-fibre filter
	Type 3, 3R, 4, 4X with chopped-fibre filter/pleated filter and hose-
	proof hood
IP protection category to IEC 60 529	IP54 with chopped-fibre filter/pleated filter
	IP55 with pleated filter and absorber mat
	IP56 with chopped-fibre filter/pleated filter and hose-proof hood
Weight/pack	0.17 kg

© Rittal 2024

2

Features

Packs of	1 pc(s).
Customs tariff number	39269097
EAN	4028177997653
ETIM 8	EC002513
ETIM 7.0	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	UL + C-UL - FTTA
	UR + C-UR (recognized)