Rittal – The System.

Faster – better – everywhere.



......

6.6

0

0

000

0

e

0

0

0

0

0

0

0

A

TS 8800.130 Support strip

State: 19/10/2024 (Source: rittal.com/com-en)



POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

TS 8800.130 - Support strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



Features

 TS 8800.130 For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment. 4.5 mm diameter hole on a 25 mm pitch pattern
contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.4.5 mm diameter hole on a 25 mm pitch pattern
Sheet steel
Zinc-plated
Assembly parts
590 mm
In enclosure width/depth 600 mm, on the inner mounting level
In enclosure height 700 mm and in enclosure width 600 mm, in conjunction with rail for interior installation AX
In enclosure width 600 mm, on the inner mounting level
In enclosure width/depth 600 mm, on the inner mounting level
In enclosure width/depth 600 mm, on the inner mounting level
In TP pedestal and one-piece console pedestal width 600 mm, in conjunction with rail for interior installation TP, compact enclosure HD

Features

To fit	Enclosure type: TS
	VX SE
	TP
	PC
	IW
	AX
	To fit width/depth: 600 mm
Packs of	20 pc(s).
Weight/pack	6.16 kg
Net weight	5.86
Gross weight	6.165
PCF/PU (cradle-to-gate)	23.5 kg CO2 eq (Cat B)
Note on the PCF class	Category B: PCF value (cradle-to-gate) approximated based on product weight and self-declared
Customs tariff number	73269098
EAN	4028177212503
ETIM 7.0	EC002620
ECLASS 8.0	27189261