Rittal – The System.

Faster – better – everywhere.





SV 9635.700 NH fuse-switch disconnector

State: 30/06/2024 (Source: rittal.com/com-en)



SV 9635.700 - NH fuse-switch disconnector Size 000

For RiLine Compact busbar system.

Features

Model No.	SV 9635.700
Function principle	
	To protect connected equipment Integral test holes provide measurement access to the contact
	parts of the fuse inserts
	For cable outlet at the top, the NH fuse-switch disconnector must be
	mounted on the board rotated through 180°
Material	Polyamide
	Fire protection corresponding to UL 94-V0
	Contact tracks: Silver-plated hard copper
Colour	RAL 7035
Coloui	KAL 7033
Test specification	IEC/DIN EN 60 947-3
For NH size	000
Rated operating current max.	125 A
Rated operating voltage	440 V (DC), 3~
	690 V (AC), 3~
Number of poles	3-pole
Cable outlet	Top/bottom
Type of electrical connection	Box terminal
Connection for round conductor	2.5 - 50 mm²
cross-sections	
Clamping area for laminated	10 x 10 mm
copper bars (W x H)	
Dimensions	Width: 49.5 mm
	Height: 174.5 mm
	Depth: 96 mm
Packs of	1 pc(s).

© Rittal 2024 2

Features

Weight/pack	0.576 kg
Copper weight (kg per piece)	0.145
Customs tariff number	85369095
EAN	4028177937604
ETIM 7.0	EC001040
ECLASS 8.0	27371401

© Rittal 2024 3