


Rittal – The System.

Faster – better – everywhere.



SV 9677.115

NH slimline fuse-switch disconnecter

State: 06/08/2024 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9677.115 - NH slimline fuse-switch disconnecter with electronic fuse monitoring

3-pole, for bar systems with 185 mm centre-to-centre spacing.

Features

Model No.	SV 9677.115
Design	3-pole, switchable
Material	Polyamide Fire protection corresponding to UL 94-V0 Contact tracks: Partially silver-plated hard copper
Colour	Chassis: RAL 7035 Cover: RAL 7001 Handle: RAL 7016
For NH size	1
For bar systems with centre-to-centre spacing	185 mm
Cable outlet	Top/bottom
Type of electrical connection	Bolt M12
Number of poles	3-pole
Rated operating voltage	400 V, 3~
Rated operating current max.	250 A
Note	When using components on busbars with contact hazard protection cover, the contact terminal must be used
Test specification	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
For converter installation	Yes
Dimensions	Width: 100 mm Height: 830 mm

Features

Connection for round conductor cross-sections	6 - 240 mm ²
---	-------------------------

To fit busbars	Height: 10 mm
----------------	---------------

Packs of	1 pc(s).
----------	----------

Weight/pack	6.02 kg
-------------	---------

Copper weight (kg per piece)	1.73
------------------------------	------

Customs tariff number	85365080
-----------------------	----------

EAN	4028177705500
-----	---------------

ETIM 7.0	EC001046
----------	----------

ECLASS 8.0	27371402
------------	----------

Approvals

Explanations	Declaration of conformity Declaration of conformity UK
--------------	---