


# Rittal – The System.

Faster – better – everywhere.



## SV 9340.700 OM adaptors

State: 27.09.2024. (Source: [rittal.com/hr-hr](http://rittal.com/hr-hr))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9340.700 - OM adaptors with connection cables

## Features

Model No.	SV 9340.700
Material	Polyamide Fire protection corresponding to UL 94-V0
Colour	Chassis: RAL 7035
Connection cables (AWG)	AWG 6
Rated current max.	65 A
Rated operating voltage	690 V, 3~
Electrical ratings UL (SCCR)	30 kA - 600 V, Fuse Class K5 max. 60 A, JDDZ/7 30 kA - 480 V, Combination Motor Controller max. 63 A, NKJH/7 65 kA - 600 V, Fuse Class J max. 60 A, JDDZ/7 65 kA - 480 V, Manual Motor Controller max. 63 A, NLRV/7 65 kA - 480 V, Combination Motor Controller max. 63 A, NKJH/7
For bar systems with centre-to-centre spacing	60 mm
Length of connection cable	130 mm
Support rail type	Metal
Note	The technical data may vary for UL applications
Number of poles	3-pole
Dimensions	Width: 75 mm Height: 208 mm
Support rails Qty/height	1 / 7.5 mm
To fit busbars	Height: 5, 10 mm
Packs of	1 pc(s).
Weight/pack	0,42 kg
Net weight	0.259
Gross weight	0.42

# Features

---

Copper weight (kg per piece)	0.116
Customs tariff number	85369095
EAN	4028177525566
ETIM 7.0	EC001531
ECLASS 8.0	27370304

---

# Approvals

---

Approvals	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK

---

# Tender text

OM adaptor 75 A  
OM adaptor 75 A with connection cable, 3-pole,  
for busbar thickness 5/10 mm and PLS 800/1600  
Technical specifications  
Connection cable: AWG 6 / approx. 16 qmm  
Construction width: 75 mm  
Length: 208 mm  
Support frame: -mm  
Support frame support: -  
Insert strips: -  
Support rail: 2  
System:  
Rittal RiLine60