

Rittal – The System.

Faster – better – everywhere.



SV 9686.000 Busbar support

State: 2024.9.27 (Source: [rittal.com/lt-en](https://www.rittal.com/lt-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9686.000 - Busbar support for busbar baying (roof section)

For baying busbar systems from enclosure to enclosure in the roof section.

Features

Model No.	SV 9686.000
Product description	For baying 3- or 4-pole flat copper busbar systems from enclosure to enclosure in the roof section.
Material	Duroplastic Fire protection corresponding to UL 94-V0
Colour	Similar to RAL 9005
Supply includes	Assembly parts
To fit busbars	30 x 10
Centre-to-centre spacing of busbars	80 mm
Assembly instruction	For the installation of max. 4 busbars (sub-conductors) per phase Cage nut (M8) 4165.500 is required to attach the busbar support to the enclosure section
Packs of	2 pc(s).
Weight/pack	4 kg
Net weight	3.8
Gross weight	3.88
Customs tariff number	85469010
EAN	4028177935631
ETIM 7.0	EC001166
ECLASS 8.0	27400607

Approvals

Approvals

DNV-GL

Lloyds Register of Shipping

Explanations

Declaration of conformity

Declaration of conformity UK