

Rittal – The System.

Faster – better – everywhere.



SK 3311.080 Rear adaptor

State: 26.9.2024 (Source: [rittal.com/si-sl](https://www.rittal.com/si-sl))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3311.080 - Rear adaptor for LCP Inline CW

May be used to close the gap that emerges when installing an LCP Inline.

Features

Model No.	SK 3311.080
Product description	May be positioned to the rear of the set forward LCP Inline CW to close the existing gap to the rear section.
Material	Sheet steel, spray-finished
Colour	RAL 7035
Supply includes	Adaptor With roof plate Assembly parts
Dimensions	Width: 300 mm Height: 2,000 mm Depth: 200 mm
To fit	Enclosure type: TS IT
Packs of	1 pc(s).
Weight/pack	22,3 kg
Net weight	21
Gross weight	22.3
EAN	4028177670242
ETIM 8	EC002515
ETIM 7.0	EC002515
ECLASS 8.0	27180712

Tender text

Rear adaptor, 3311.080
for TopTherm LCP CW 3311.530/560

Rear adaptor:

For optimum air routing and for energy efficient operation the LCP Inline units protrude 200 mm in front of the server racks.

To fill the gap in the rear section, the adaptor is screw-fastened onto the rear of the LCP to create a uniform view.

Rear adaptor, supply includes:

Adaptor frame incl. assembly parts

Colour RAL 7035