

# Rittal – The System.

Faster – better – everywhere.



## KEL 9401.600 Ex enclosures

State: 19.10.2024 (Source: [rittal.com/si-sl](https://www.rittal.com/si-sl))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# KEL 9401.600 - Ex enclosures Stainless steel, empty enclosure with hinged door

Ex enclosure with hinged door, stainless steel

## Features

|                                     |   |
|-------------------------------------|---|
| Model No.                           | KEL 9401.600  |
| Design                              | Ex enclosures   |
| Material                            | Enclosure: Stainless steel 1.4301 (AISI 304)<br>Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal<br>Mounting plate: Sheet steel |
| Surface finish                      | Enclosure: Brushed, grain 400, peak-to-valley height < 0.8 µm<br>Mounting plate: Zinc-plated  |
| Supply includes                     | Enclosure<br>Door<br>Mounting plate   |
| Dimensions                          | Width: 200 mm<br>Height: 300 mm<br>Depth: 155 mm  |
| Dimensions mounting plate (W x H)   | 162 mm x 275 mm   |
| Certificate IEC EX PTB 09.0035U     | Yes   |
| Certificate PTB 02 ATEX 1082U       | Yes   |
| Basic material                      | Stainless steel 1.4301 (AISI 304)   |
| Lock                                | Lock version: Cam<br>Number of locks: 1<br>Lock insert: 3 mm double-bit   |
| IP protection category to IEC 60529 | IP 66   |
| Protection category NEMA            | NEMA 4X   |

# Features

---

|                       |  |
|-----------------------|--|
| Type rating to UL 50E | Type 1<br>Type 4<br>Type 4X<br>Type 12 |
|-----------------------|--|

---

|          |          |
|----------|----------|
| Packs of | 1 pc(s). |
|----------|----------|

---

|             |      |
|-------------|------|
| Weight/pack | 5 kg |
|-------------|------|

---

|            |   |
|------------|---|
| Net weight | 4 |
|------------|---|

---

|              |      |
|--------------|------|
| Gross weight | 4.28 |
|--------------|------|

---

|                       |          |
|-----------------------|----------|
| Customs tariff number | 94032080 |
|-----------------------|----------|

---

|     |               |
|-----|---------------|
| EAN | 4028177138681 |
|-----|---------------|

---

|          |          |
|----------|----------|
| ETIM 7.0 | EC002503 |
|----------|----------|

---

|            |          |
|------------|----------|
| ECLASS 8.0 | 27180502 |
|------------|----------|

---

# Approvals

---

|           |   |
|-----------|---|
| Approvals | ATEX<br>CQC-CCC<br>IEC Ex<br>UL + C-UL (listed) |
|-----------|---|

---

|              |                            |
|--------------|----------------------------|
| Explanations | Manufacturer's declaration |
|--------------|----------------------------|

---