Rittal – The System.

Faster – better – everywhere.





VX 8952.010 Isolator door cover

State: 26.06.2024 (Source: rittal.com/ua-en)



VX 8952.010 - Isolator door cover for VX

Including main door latch for safety locking of enclosures and bayed enclosure suites in accordance with UL regulations. Tested in conjunction with an actuator lever for master switches from the following companies: Allen Bradley, Square D, General Electric, Eaton, Siemens.

Features

Model No.	VX 8952.010
Product description	Including main door latch for safety locking of enclosures and bayed enclosure suites in accordance with UL regulations. Tested in conjunction with an actuator lever for master switches from the following companies: Allen Bradley, Square D, General Electric, Eaton, Siemens.
Benefits	Meets the requirements of UL 508 A In conjunction with the operating mechanism, adjacent door lock and interconnecting rods, these requirements are also met for bayed combinations May be mounted optionally on the left or right of the enclosure. With this cover, all single-door bayed enclosures may be configured as isolator door enclosures. The complete installation surface of the enclosure is retained. In conjunction with the mounting plate infill, the mounting surface of the main enclosure can be enlarged by up to 14%.
	Two cut-outs for actuator levers on the front, for internal mounting at varying heights

© Rittal 2024 2

Features

Sien	9477-0CK12 for 3VA53/54/63/64 up to 600 A, plastic actuator, IA 1, 12, 3R, black=OFF, red=ON 9477-0CK12 for 3VA53/54/63/64 up to 600 A, epoxy-coated I actuator, NEMA 1, 12, 3R, black=OFF, red=ON
	nens: Depth-variable operating mechanism – complete kits 9138-0DK72, 3VA9138-0DK82, 3VA9138-0DK84 9278-0DK72, 3VA9278-0DK82, 3VA9278-0DK84 9478-0DK72, 3VA9478-0DK82, 3VA9478-0DK84
Material Stair	nless steel 1.4301 (AISI 304), 1.5 mm
Supply includes Mair	n door lock, cover plate and assembly parts.
Heig	th: 103 mm yht: 2,000 mm th: 600 mm
	er may only be mounted on a single-door enclosure with tubular r frame
Type rating to UL 50E Type Type	
Protection category to IEC 60 529 IP 5	5 in conjunction with enclosures from the VX series
Protection category NEMA NEM	1A 12 (in conjunction with enclosures from the VX series)
Packs of 1 pc	(s).
Weight/pack 19.4	· ka
Customs tariff number 9403	•

© Rittal 2024 3

Features

EAN	4028177944695
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Approvals UL + C-UL (listed)

© Rittal 2024 4