

Rittal – The System.

Faster – better – everywhere.



SV 9676.700 Connection plate

State: 26/09/2024 (Source: rittal.com/uk-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9676.700 - Connection plate for ring terminals

For connecting ring terminals to a Flat-PLS busbar system with 2 – 4 bars per conductor.

Features

Model No.	SV 9676.700
Product description	For connecting ring terminals to a busbar distributor system made from flat copper. Suitable for 10 mm bar thickness.
Material	Connection plate: E-Cu, nickel-plated Busbar claw: Stainless steel
Supply includes	Assembly parts (excluding screws) Grub screw
Assembly instruction	The required screw length must be selected in line with the busbar width W, i.e. length = W + fastening measurement. Screws are not included with the supply. Busbar claw with threaded insert M10
Number of bars per conductor	2
Dimensions	Thread: M12
Mounting dimensions	20 mm
Packs of	1 pc(s).
Weight/pack	0.62 kg
Copper weight (kg per piece)	0.49
Customs tariff number	85369010
EAN	4028177625754
ETIM 7.0	EC001900
ECLASS 8.0	27400613

Approvals

Approvals

Approvals

ABS

DNV-GL

Lloyds Register of Shipping

Explanations

Declaration of conformity

Declaration of conformity UK