

# Rittal – The System.

Faster – better – everywhere.



## SK 3188.940

## Wall-mounted cooling unit Blue e+

State: 7/3/2024 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3188.940 - Wall-mounted cooling unit Blue e+ 5459.43 - 19790.42 BTU/h

Energy-efficient Blue e+ wall-mounted cooling units in the 5459.43 - 19790.42 BTU/h power classes. By using speed-controlled components and heat pipe technology, they achieve an average energy saving of 75%. Available in carbon steel and stainless steel.



## Features

Model No.	SK 3188.940
Benefits	<ul style="list-style-type: none"><li>An average of 75% energy savings due to speed-regulated components and heat pipe technology</li><li>Suitable for international use due to a unique multi-voltage capability</li><li>Longer service life of the components inside the enclosure and the cooling unit due to component-friendly cooling</li><li>Intuitive operation due to touch display and intelligent interfaces</li></ul>
Material	Carbon steel
Color	RAL 7035
Supply includes	<ul style="list-style-type: none"><li>Condenser with hydrophobic RiNano coating</li><li>Integral electric condensate evaporation</li><li>Assembly components</li><li>Wired ready for connection (plug-in terminal strip)</li></ul>
Options	<ul style="list-style-type: none"><li>For remote monitoring and networking of cooling units and chillers, use the Blue e+ Generation IoT Interface, item number 3124.300.</li><li>Increase machine availability and process safety by remote monitoring of device data, condition, and system messages.</li></ul>

# Features

Total cooling output to DIN EN 14511	Cooling output L35 L35/50 Hz: 4.2 kW Cooling output L35 L35/60 Hz: 4.2 kW Cooling output L35 L50/50 Hz: 3.02 kW Cooling output L35 L50/60 Hz: 3.02 kW Cooling output L35 L35/50 Hz: 14,331 BTU/h Cooling output L35 L35/60 Hz: 14,331 BTU/h Cooling output L35 L50/50 Hz: 10,305 BTU/h Cooling output L35 L50/60 Hz: 10,305 BTU/h
Rated operating voltage	380 V - 480 V, 3~, 50 Hz/60 Hz
Note	Please observe the assembly instructions. When the software is downloaded, a contract is concluded between the contractual partner and Rittal for the free use of the software in accordance with these license conditions. Only for semi-outdoor use (see instructions for description)
Note on Model No.:	Tolerance: 380 V -10% (342 V) and 480 V +5% (509 V) Full internal mounting not possible
Rated output	1.3 kW
Air throughput (unimpeded air flow)	External circuit: 2,300 m <sup>3</sup> /h Internal circuit: 2,300 m <sup>3</sup> /h External circuit: 1,353.7 cfm Internal circuit: 1,353.7 cfm
Energy efficiency ratio (EER) 50/60 Hz L35 L35	Refrigeration factor L35 L35 (EER) 50 Hz: 3.46 Refrigeration factor L35 L35 (EER) 60 Hz: 3.46
Seasonal energy efficiency ratio (SEER) 50/60 Hz	8.1
Version	wall-mounted
Dimensions	Width: 450 mm Height: 1,600 mm Depth: 393 mm Width: 17.7 " Height: 63 " Depth: 15.5 "
Required mounting cut-out	Width of opening: 433 mm Cut-out height: 1,579 mm Width of opening: 17 " Cut-out height: 62.2 "

# Features

Protection category IP to EN 60529	Internal circuit IP 55
Protection category NEMA	UL Type 3R/12
Refrigerant/cooling medium	Refrigerant: R134a Quantity: 1.75 kg Global Warming Potential (GWP): 1,430 CO2 equivalent (CO2e): 2.5 t Refrigerant: R134a Quantity: 3.9 lb.
Temperature control	e+ controller (factory setting +35 °C)
Operating temperature range	-20 °C...60 °C -4 °F...140 °F
Storage temperature range	-40 °C...70 °C -40 °F...158 °F
Operating temperature range of refrigerant circuit (active)	3 °C...60 °C
Operating temperature range of heat pipe	-20 °C...45 °C
Setting range	20 °C...50 °C 68 °F...122 °F
Rated power Pel	Rated power L35 L35/50 Hz: 1.21 kW Rated power L35 L35/60 Hz: 1.21 kW Rated power L35 L50/50 Hz: 1.28 kW Rated power L35 L50/60 Hz: 1.28 kW
Permissible operating pressure (p. max.)	24 bar 348.1 PSI
Packaging unit	1 pc(s).
Weight/packaging unit	72.4 kg 159.6 lb.
Customs tariff number	84158200
EAN	4028177709591
E-Number Sweden	E3404501

# Features

---

ETIM 7.0	EC000855
----------	----------

---

ECLASS 8.0	27180704
------------	----------

# Approvals

---

Approvals	IEC CB UL + C-UL (listed) UL + C-UL - FTTA
-----------	--

---

Certificates	EAC
--------------	-----

---

Explanations	Declaration of conformity Declaration of conformity UK
--------------	---