Rittal – The System.

Faster - better - everywhere.





SK 3238.200 Outlet Filters

State: 7/23/2024 (Source: rittal.com/us-en)



SK 3238.200 - Outlet Filters Standard

For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.



Features

Model No.	SK 3238.200
Product description	For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.
Material	ABS
Color	RAL 7035
Supply includes	Outlet Filters
	Fleece filter mat
Mounting cut-out	Width of opening: 124 mm
	Cut-out height: 124 mm
	Width of opening: 4.88 "
	Cut-out height: 4.88 "
Suitable for Model No.	SK 3238.1xx
Dimensions	Width: 148.5 mm
	Height: 148.5 mm
	Depth: 24 mm
	Width: 5.85 "
	Height: 5.85 "
	Depth: 0.94 "
Protection category NEMA	Type 1 with folded filter
	Torre 10 with flaces flace
	Type 12 with fleece filter

© Rittal 2024

2

Features

Protection category IP to IEC 60 529	IP54 with fleece filter/folded filter IP55 with folded filter and absorber mat IP56 with fleece filter/folded filter and hose-proof hood
Weight/packaging unit	0.18 kg 0.4 lb.
Packaging unit	1 pc(s).
Customs tariff number	39269097
EAN	4028177651739
E-Number Sweden	E3404349
ETIM 8	EC002513
ETIM 7.0	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	CSA
	UL + C-UL - FTTA
	UR + C-UR (recognized)
Certificates	EAC
Explanations	Declaration of conformity

© Rittal 2024 3