
Rittal – The System.

Faster - better - everywhere.





TS 8800.130 Support Strip

State: 9/26/2024 (Source: rittal.com/us-en)



TS 8800.130 - Support Strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.







2

Features

TS 8800.130
For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.
4.5 mm diameter hole on a 25 mm hole pattern
Carbon steel
Zinc-plated
Assembly components
590 mm 23.2 ″
In enclosure width/depth 600 mm, on the inner mounting level
In enclosure height 700 mm and in enclosure width 600 mm, in conjunction with rail for interior installation AX
In enclosure width 600 mm, on the inner mounting level
In enclosure width/depth 600 mm, on the inner mounting level
In enclosure width/depth 600 mm, on the inner mounting level
In TP pedestal and one-piece console pedestal width 600 mm, in conjunction with rail for interior installation TP, compact enclosure HD

© Rittal 2024

Features

Suitable for	Enclosure type: TS
	VX SE
	TP
	PC
	IW
	AX
	Suitable for width/depth: 600 mm
	Enclosure type: TS
	VX SE
	TP
	PC
	IW
	AX
	Suitable for width/depth: 23.6 ″
Packaging unit	20 pc(s).
Weight/packaging unit	6.16 kg
	13.6 lb.
Net weight	5.86
Gross weight	6.165
PCF/PU (Cradle-to-Gate)	23.5 kg CO2 eq (Cat B)
Note on the PCF class	Category B: PCF value (cradle-to-gate) approximated based on product weight and self-declared
Customs tariff number	73269098
EAN	4028177212503
ETIM 7.0	EC002620
ECLASS 8.0	27189261

© Rittal 2024 3